

Press-locked gratings HIGH-SOLID HIGH-STRENGTH STEEL STRIP

WAREHOUSE PROGRAMME / SUPPLIER PROGRAMME

Industry-standard press-locked gratings by ProMetall, High-Solid high-strength steel strip, hot-dip-galvanised in accordance with DIN EN ISO 1461

STAIRTREADS (MM)	Mesh	ВВ	Delivery
500 x 195	31 x 31	25 x 2	L
500 x 195	31 x 31	25 x 2	X
600 x 195	31 x 31	25 x 2	L
600 x 195	31 x 9	25 x 2	X
600 x 193	31 x 31	25 x 2	L
600 x 240	31 x 31	25 x 2	X
			L
600 x 270 600 x 270	31 x 31	25 x 2	X
	31 x 9 31 x 31	25 x 2	
600 x 305		25 x 2	L
600 x 305	31 x 9	25 x 2	X
700 x 195	31 x 31	25 x 2	L
700 x 195	31 x 9	25 x 2	X
700 x 240	31 x 31	25 x 2	L
700 x 240	31 x 9	25 x 2	X
800 x 195	31 x 31	25 x 2	L
800 x 195	31 x 9	25 x 2	L
800 x 240	31 x 31	25 x 2	L
800 x 240	31 x 9	25 x 2	L
800 x 270	31 x 31	25 x 2	L
800 x 270	31 x 9	25 x 2	L
800 x 305	31 x 31	25 x 2	L
800 x 305	31 x 9	25 x 2	L
900 x 195	31 x 31	30 x 2	L
900 x 195	31 x 9	30 x 2	X
900 x 240	31 x 31	30 x 2	L
900 x 240	31 x 9	30 x 2	X
900 x 270	31 x 31	30 x 2	L
900 x 270	31 x 9	30 x 2	L
900 x 305	31 x 31	30 x 2	L
900 x 305	31 x 9	30 x 2	X
1000 x 195	31 x 31	30 x 2	L
1000 x 195	31 x 9	30 x 2	X
1000 x 240	31 x 31	30 x 2	L
1000 x 240	31 x 9	30 x 2	L
1000 x 270	31 x 31	30 x 2	L
1000 x 270	31 x 9	30 x 2	L
1000 x 305	31 x 31	30 x 2	L
1000 x 305	31 x 9	30 x 2	L
1100 x 195	31 x 31	40 x 2	L
1100 x 240	31 x 31	40 x 2	L
1100 x 270	31 x 31	40 x 2	L
1100 x 270	31 x 9	40 x 2	L
1100 x 305	31 x 31	40 x 2	L
1100 x 305	31 x 9	40 x 2	L
1200 x 195	31 x 31	40 x 2	L
1200 x 195	31 x 9	40 x 2	X
1200 x 240	31 x 31	40 x 2	L
1200 x 240	31 x 9	40 x 2	L
1200 x 270	31 x 31	40 x 2	L
1200 x 270	31 x 9	40 x 2	L
1200 x 305	31 x 31	40 x 2	L
1200 x 305	31 x 9	40 x 2	L

PLATFORMS (MM)	Mesh	ВВ	Delivery
300 x 998	31 x 31	30 x 2	L
500 x 998	31 x 31	25 x 2	L
500 x 998	31 x 9	25 x 2	L
500 x 998	31 x 31	30 x 2	L
500 x 998	31 x 9	30 x 2	L
600 x 998	31 x 31	25 x 2	L
600 x 998	31 x 31	30 x 2	L
600 x 998	31 x 9	30 x 2	L
700 x 998	31 x 31	25 x 2	L
700 x 998	31 x 31	30 x 2	L
700 x 998	31 x 9	30 x 2	L
800 x 998	31 x 31	25 x 2	L
800 x 998	31 x 9	25 x 2	L
800 x 998	31 x 31	30 x 2	L
800 x 998	31 x 9	30 x 2	L
900 x 998	31 x 31	25 x 2	L
900 x 998	31 x 31	30 x 2	L
900 x 998	31 x 9	30 x 2	L
1000 x 998	31 x 31	25 x 2	L
1000 x 998	31 x 31	30 x 2	L
1000 x 998	31 x 9	30 x 2	L
1100 x 998	31 x 31	30 x 2	L
1100 x 998	31 x 9	30 x 2	L
1200 x 998	31 x 31	30 x 2	L
1200 x 998	31 x 9	30 x 2	L

TRAPEZOIDAL (MM)	Mesh	ВВ	Delivery
100/290 x 540	31 x 31	30 x 2	L
100/360 x 685	31 x 31	30 x 2	L
100/360 x 685	31 x 9	25 x 2	L
100/390 x 835	31 x 31	30 x 2	L
100/390 x 835	31 x 9	25 x 2	L
100/430 x 935	31 x 31	30 x 2	L
100/430 x 935	31 x 9	25 x 2	L
100/455 x 1010	31 x 31	30 x 2	L
100/475 x 1060	31 x 31	30 x 2	L

also in stock ungalvanised, anti-slip design, available for delivery with/without SAK

RAW PANELS (MM)	Mesh	BB	Delivery
3000 x 1350	31 x 31	30 x 2	L
3000 x 1350	31 x 9	30 x 2	L

Press-locked mats S235JR raw (ungalvanised) without border framing

FIXING CLIPS		Delivery
upper-+lower part+screw	for Mesh 31 x 31	L
upper-+lower part+screw	for Mesh 31 x 9	L
upper-+lower part+screw	for Mesh 20 x 20	L
Double fixing clips	for Mesh 31 x 31	L
Double fixing clips	for Mesh 31 x 9	L

Industry standard stair treads with side plate perforation in accordance with DIN 24531

industry standard gratings with endings made of u-profile L = Supply within 5 - 7 working days L = 24/48 hours supplier service all over Austria

L = 24/48 hours supplier service all over Austria

L = Supply within 5 - 7 working days



Press-locked gratings STEEL ST37/S235JR

WAREHOUSE PROGRAMME / SUPPLIER PROGRAMME

Industry-standard press-locked gratings by ProMetall, steel S235JR, hot-dip galvanised in accordance with DIN EN ISO 1461

STAIRTREADS (MM)	Mesh	BB	Delivery
600 x 240	31 x 31	30 x 2	X
600 x 240	31 x 9	30 x 2	X
600 x 270	31 x 31	30 x 2	L
600 x 270	31 x 9	30 x 2	X
600 x 305	31 x 31	30 x 2	X
600 x 305	31 x 9	30 x 2	X
700 x 240	31 x 31	30 x 2	X
700 x 240	31 x 9	30 x 2	X
800 x 240	31 x 31	30 x 2	L
800 x 240	31 x 9	30 x 2	X
800 x 270	31 x 31	30 x 2	L
800 x 270	31 x 9	30 x 2	L
800 x 305	31 x 31	30 x 2	X
800 x 305	31 x 9	30 x 2	X
900 x 240	31 x 31	30 x 2	X
900 x 240	31 x 9	30 x 2	X
900 x 270	31 x 31	30 x 2	X
900 x 270	31 x 9	30 x 2	X
900 x 305	31 x 31	30 x 2	X
900 x 305	31 x 9	30 x 2	X
1000 x 240	31 x 31	30 x 3	L
1000 x 240	31 x 9	30 x 3	L
1000 x 270	31 x 31	30 x 3	L
1000 x 270	31 x 9	30 x 3	L
1000 x 305	31 x 31	30 x 3	L
1000 x 305	31 x 9	30 x 3	L
1100 x 240	31 x 31	40 x 3	X
1100 x 270	31 x 31	40 x 3	X
1100 x 270	31 x 9	40 x 3	X
1100 x 305	31 x 31	40 x 3	X
1100 x 305	31 x 9	40 x 3	X
1200 x 240	31 x 31	40 x 3	X
1200 x 240	31 x 9	40 x 3	X
1200 x 270	31 x 31	40 x 3	L
1200 x 270	31 x 9	40 x 3	L
1200 x 305	31 x 31	40 x 3	L
1200 x 305	31 x 9	40 x 3	L

Industry standard stair treads with side plate perforation in accordance with DIN 24531

DESIGN SLIP-RESISTANT: Cross bars serrated

L = 24/48 hours supplier service all over Austria X = Supply within 15 - 20 working days Subject to change

PLATFORMS (MM)	Mesh	BB	Delivery
500 x 998	31 x 31	25 x 2	X
500 x 998	31 x 9	25 x 2	X
500 x 998	31 x 31	30 x 2	L
500 x 998	31 x 9	30 x 2	Х
600 x 998	31 x 31	25 x 2	L
600 x 998	31 x 31	30 x 2	L
600 x 998	31 x 9	30 x 2	X
700 x 998	31 x 31	25 x 2	Х
700 x 998	31 x 31	30 x 2	L
700 x 998	31 x 9	30 x 2	Χ
800 x 998	31 x 31	25 x 2	X
800 x 998	31 x 9	25 x 2	X
800 x 998	31 x 31	30 x 2	L
800 x 998	31 x 9	30 x 2	L
900 x 998	31 x 31	30 x 2	Χ
900 x 998	31 x 31	30 x 2	L
900 x 998	31 x 9	30 x 2	X
1000 x 998	31 x 31	30 x 2	L
1000 x 998	31 x 9	30 x 2	L
1000 x 998	31 x 31	30 x 3	L
1100 x 998	31 x 31	30 x 2	Х
1100 x 998	31 x 9	30 x 2	Х
1200 x 998	31 x 31	30 x 2	Х
1200 x 998	31 x 9	30 x 2	Х
1200 x 998	31 x 31	30 x 3	L

Industry standard gratings with edgings made of T-profile

L = 24/48 hours supplier service all over Austria

X =Supply within 15 - 20 working days

Subject to change

RAW PANELS (MM)	Mesh	ВВ	Delivery
3000 x 1350	31 x 31	30 x 2	L
3000 x 1350	31 x 9	30 x 2	L

Press-locked mats S235JR raw (ungalvanised) without border framing

FIXING CLIPS		Delivery
upper-+lower part+screw	for Mesh 31 x 31	L
upper-+lower part+screw.	for Mesh 31 x 9	L
upper-+lower part+screw	for Mesh 20 x 20	L
Double fixing clips	for Mesh 31 x 31	L
Double fixing clips	for Mesh 31 x 9	L



Perforated safety panels by ProMetall


hot-dip galvanised in accordance with DIN EN ISO 1461 Panels are welded into gratings, border framing 30/3 mm

STEEL 2 mm, hot-dip galvanised	Length x width	height
Article description	(mm)	(mm)
Safety panels hot-dip galvanised	1000 x 500	32
Safety panels hot-dip galvanised	1000 x 600	32
Safety panels hot-dip galvanised	1000 x 700	32
Safety panels hot-dip galvanised	1000 x 750	32
Safety panels hot-dip galvanised	1000 x 800	32
Safety panels hot-dip galvanised	1000 x 900	32
Safety panels hot-dip galvanised	1000 x 1000	32
Safety panels hot-dip galvanised	1000 x 1200	32

Perforated safety panels by ProMetall

Steel, raw - untreated - for DIY

STEEL 2 mm, raw - untreated	Length x width	height
Article description	(mm)	(mm)
Safety panels	3000 x 50	32
Safety panels	3000 x 75	32
Safety panels	3000 x 100	32
Safety panels	3000 x 125	32
Safety panels	3000 x 150	32
Safety panels	3000 x 200	32
Safety panels	3000 x 150	45
Safety panels	3000 x 200	45
Safety panels	3000 x 250	45
Safety panels	3000 x 300	45
Safety panels	further panels available	45



Perforated safety panels by ProMetall

Stainless steel, 2 mm, raw - untreated

STAINLESS STEEL 1.4301	Length x width	height
Article description	(mm)	(mm)
Safety panels 1.4301	3000 x 50	32
Safety panels 1.4301	3000 x 75	32
Safety panels 1.4301	3000 x 100	32
Safety panels 1.4301	3000 x 125	32
Safety panels 1.4301	3000 x 150	32
Safety panels 1.4301	3000 x 200	32
Safety panels 1.4301	3000 x 150	45
Safety panels 1.4301	3000 x 200	45
Safety panels 1.4301	3000 x 250	45

Supply within 5 - 7 working days Subject to change



Perforated safety stair treads by ProMetall

hot-dip galvanised in accordance with DIN EN ISO 1461, incl. perforated side covers

STEEL 2 mm, hot-dip galvanised	Length x height	Width 200	Width 250	Width 275	Width 300
Article description	(mm)	(mm)	(mm)	(mm)	(mm)
Safety stair treads hot-dip galvanised		L	L		
Safety stair treads hot-dip galvanised	600 x 45	L	L	L	L
Safety stair treads hot-dip galvanised		L	L	L	L
Safety stair treads hot-dip galvanised	800 x 45	L	L	L	L
Safety stair treads hot-dip galvanised	900 x 45	L	L	L	L
Safety stair treads hot-dip galvanised	1000 x 45	L	L	L	L
Safety stair treads hot-dip galvanised	1100 x 57	L	L	L	L
Safety stair treads hot-dip galvanised	1200 x 57	L	L	L	L
Safety stair treads hot-dip galvanised	1500 x 57	L	L	L	L

Perforated safety stair treads by ProMetall

Stainless steel 1.4301 pickled, incl. perforated side covers


STAINLESS STEEL 1.4301	Length x height	Width 200	Width 250	Width 275	Width 300
Article description	(mm)	(mm)	(mm)	(mm)	(mm)
Safety stair tread 1.4301	600 x 45	L	L	L	L
Safety stair tread 1.4301	800 x 45	L	L	L	L
Safety stair tread 1.4301	1000 x 45	L	L	L	L

Perforated safety stair treads by ProMetall

Aluminium 3 mm, natural anodised, incl. perforated side covers

ALUMINIUM (Almg3)	Length x height	Width 200	Width 250	Width 275
Article description	(mm)	(mm)	(mm)	(mm)
Safety stair treads	600 x 65.5	L	L	
Safety stair treads	800 x 65.5	L	L	L
Safety stair treads	1000 x 65.5	L	L	L
Safety stair treads	1200 x 65.5			L

Supply within 5 - 7 working days Subject to change






Forge-welded gratings STEEL ST37/S235JR

WAREHOUSE PROGRAMME / SUPPLIER PROGRAMME

Industry-standard press-locked gratings by ProMetall, steel S235JR, hot-dip galvanised in accordance with DIN EN ISO 1461

STAIRTREADS (MM)	Mesh	BB	Delivery
600 x 240	34 x 38	30 x 2	X
600 x 270	34 x 38	30 x 2	X
600 x 305	34 x 38	30 x 2	X
700 x 240	34 x 38	30 x 2	X
700 x 270	34 x 38	30 x 2	X
800 x 240	34 x 38	30 x 2	X
800 x 270	34 x 38	30 x 2	L
800 x 305	34 x 38	30 x 2	X
900 x 240	34 x 38	30 x 2	X
900 x 270	34 x 38	30 x 2	X
900 x 305	34 x 38	30 x 2	X
1000 x 240	34 x 38	30 x 3	X
1000 x 270	34 x 38	30 x 3	L
1000 x 305	34 x 38	30 x 3	X
1100 x 240	34 x 38	40 x 3	X
1100 x 270	34 x 38	40 x 3	X
1100 x 305	34 x 38	40 x 3	X
1200 x 240	34 x 38	40 x 3	X
1200 x 270	34 x 38	40 x 3	X
1200 x 305	34 x 38	40 x 3	X



PLATFORMS (MM)	Mesh	BB	Delivery
500 x 998	34 x 38	30 x 3	L
600 x 998	34 x 38	30 x 2	L
600 x 998	34 x 38	30 x 3	L
700 x 998	34 x 38	30 x 2	L
700 x 998	34 x 38	30 x 3	L
800 x 998	34 x 38	30 x 2	L
800 x 998	34 x 38	30 x 3	L
900 x 998	34 x 38	30 x 2	L
900 x 998	34 x 38	30 x 3	L
1000 x 998	34 x 38	30 x 2	L
1000 x 998	34 x 38	30 x 3	L
1200 x 998	34 x 38	30 x 2	L
1200 x 998	34 x 38	30 x 3	L

Industry standard gratings with edging made of flat iron L= Supply within 5-10 working days Subject to change

RAW PANELS (MM)	Mesh	BB	Delivery
6100 x 1000	34 x 38	30 x 2	L
6100 x 1000	34 x 38	30 x 3	L
6100 x 1000	34 x 38	40 x 3	L
3050 x 1000	34 x 38	30 x 2	L
3050 x 1000	34 x 38	30 x 3	L
3050 x 1000	34 x 38	40 x 3	L

Forge-welded panels made of steel S235JR raw (ungalvanised) without border frame $\,$

FIXING CLIPS		Delivery
upper-+lower part+screw	for Mesh 34 x 38	L
upper-+lower part+screw	for Mesh 31 x 9	L
upper-+lower part+screw	for Mesh 20 x 20	L
Double fixing clips	for Mesh 31 x 31	L
Double fixing clips	for Mesh 31 x 9	L

Industry standard steps with side plate perforation in accordance with DIN 24531


L = Supply within 5 - 7 working days

X =Supply within 15 - 20 working days

Subject to change



Safety gratings PERFORATED GRATINGS



ProMetall safety ladder rungs

STEEL - raw	Measurements LxWxH	Delivery
Туре	(mm)	
A - 25x32	2000 x 25 x 32	L
B - 30x32	2000 x 30 x 32	L
C - 50x32	3000 x 50 x 32	L
A - 30x25	300 x 30 x 25	L
A - 30x25	400 x 30 x 25	L

STAINLESS STEEL		
1.4301	Measurements LxWxH	Delivery
Туре	(mm)	
B - 30x32	2000 x 30 x 32	L
C - 50x32	3000 x 50 x 32	L
A - 30x25	300 x 30 x 25	L
A - 30x25	400 × 30 × 25	L

STAINLESS STEEL		
1.4301	Measurements LxWxH	Delivery
Туре	(mm)	
B - 30x32	2000 x 30 x 32	L
C - 50x32	3000 x 50 x 32	L
A - 30x25	300 x 30 x 25	L
A - 30x25	400 x 30 x 25	L


STAINLESS STEEL		
1.4404	Measurements LxWxH	Delivery
Туре	(mm)	
B - 30x32	2000 x 30 x 32	L
C - 50x32	3000 x 50 x 32	L
A - 30x25	300 x 30 x 25	L
A - 30x25	400 x 30 x 25	L

L = 24/48 hours supplier service all over Austria

L = Supply within 5 - 7 working days

Subject to change





ProMetall Swimming pool stair treads

Untreated design with anti-slip nozzle perforation (pos.1+2 with shrink-wrapped side elements – for pipe diameter 40 mm)

Size in mm	Raw material	kg/unit	Artno.
530 x 70, 15°/ 22.5° / 90°/ no cutout	1.4404	0.70	8V2A1
530 x 70, 15°/ 22.5° / 90°/ no cutout	1.4404	0.70	8V2A1
600 x 250	1.4404	3.30	8V2A2
600 x 250	1.4404	3.30	8V2A2
800 x 250	1.4404	4.70	8V2A3
800 x 250	1.4404	4.70	8V2A3
1000 x 250	1.4404	5.50	8V2A4
1000 x 250	1.4404	5.50	8V2A4

Supply period: 5 – 7 working days

Accessories

Material 1.4301 or 1.4404 each with protective foil	
Rosettes	Flange
Diameter 96 high/perforated Diam. 40	Diam. 104 x 4/perforated in the middle
Diameter 96 high/perforated Diam. 43	Diameter 104x4/not perforated
Diameter 96 high/not perforated	Diameter 89x4/perforated
Diameter 96 flat/perforated Diam. 40	Diameter 89x4/not perforated
Diameter 96 flat/perforated Diam. 43	Diameter 55x4/perforated
Diameter 96 flat/not perforated	Diameter 55x4/not perforated
Diameter 60 perforated Diam. 16	
Diameter 60 high/not perforated or other	

