

Profile edgings for perforated metal sheets





Your advantage: All positions available at all times! Rod length generally 3000 mm

Description	Slot width (mm)	Wall thickness (mm)	Material	Weight (kg/lfm)
ProMetall			St37-2	
R 18 – 1.7	1.70	1.25	St37-2	0.46
E 20 x 20 – 1.7	1.70	1.25	St37-2	0.53
R 27 – 1.7	1.70	1.50	St37-2	1.15
E 20 x 30 – 1.7	1.70	1.50	St37-2	1.27

R 18 – 1.7	1.70	1.25	SVZ	0.46
E 20 x 20 – 1.7	1.70	1.25	SVZ	0.53
R 27 – 1.7	1.70	1.50	SVZ	1.15
E 20 x 30 – 1.7	1.70	1.50	SVZ	1.27

R 18 – 1.7	1.70	1.25	Al 99.5	0.16
E 20 x 20 – 1.7	1.70	1.25	Al 99.5	0.19
R 27 – 1.7	1.70	1.50	Al 99.5	0.45
E 20 x 30 – 1.7	1.70	1.50	Al 99.5	0.45

R 18 – 1.7	1.70	1.25	1.4301	0.46
R 18 – 1.7	1.70	1.25	1.4301 sanded	0.46
E 20 x 20 – 1.7	1.70	1.25	1.4301	0.53
R 27 – 1.7	1.70	1.50	1.4301	1.15
R 27 – 1.7	1.70	1.50	1.4301 sanded	1.15
E 20 x 30 – 1.7	1.70	1.50	1.4301	1.27
E 20 x 30 – 1.7	1.70	1.50	1.4301 sanded	1.27



Profile edgings for crimp screens and expanded metal

WG 30 x 30	5.7	1.5	St37-2	1.48
WG 40 x 40	7.5	2	St37-2	2.47

